

**Belt Agilo**

Nº Ed/Rev  
01

Date:  
02/07/2025

**Technical specifications**

- **Material:** TPV (Weather and UV resistant)
- **Tree Diameter Application:** 40 mm – 100 mm
- **Strap Length:** 314 mm ± 0.5 mm
- **Color:** Black
- **Elasticity:** 77 Shore A
- **Mounting:** Wall or structure-mounted using M6 countersunk screws
- **Fit:** Confirm wall material complies with structural load requirements
- **Design:** Cylindrical force distribution for balanced load



**Working conditions**

- **Recommended Use:** Tree nurseries
- **Crop Applications:** Fruit trees, olive trees, ornamental trees, and others
- **Temperature Range:** -20 °C to +50 °C
- **Humidity Range:** 0–100%
- **Chemical Exposure:** Use of chemical products may affect performance
- **UV Protection:** Yes

**Instructions of use**

1. **Fix the product to the wall support** using **M6 countersunk screws** through the designated mounting holes.
2. **Position the Agilo Belt** around the **tree trunk**.
3. **Ensure the belt is properly tensioned** and the **tree is stabilized**.
4. **The conical design** ensures **balanced load distribution** and **minimizes stress** on the tree.
5. **Installation is quick and robust**, suitable for **various weather conditions**.
6. **When the tree is removed**, the **Agilo system remains installed**, ready to support the next tree.

**Stocking conditions**

- Stock the boxes in a dry and fresh place

- The product specifications are subject to change without notice to improve reliability, function or design or otherwise.  
- It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Replaces the Ed/Rev. Nº- Dated: -