

Pipe Agilo

N° Ed/Rev
01

Date:
02/07/2025

Technical specifications

- **Material:** TPV (Weather and UV resistant)
- **Tree Diameter Application:** 40 mm – 100 mm
- **Strap Length:** 314 mm ± 0.5 mm
- **Strap Height:** 26.5 mm ± 0.5 mm
- **Color:** Black
- **Elasticity:** 77 Shore A
- **Design:** Conical joint between belts, with integrated adjustable buckle and curved tip
- **Integrated Straps:** Adjustable, tree-friendly fastening system



Working conditions

- **Recommended Use:** Tree nurseries
- **Crop Applications:** Fruit trees, olive trees, ornamental trees, and others
- **Temperature Range:** -20 °C to +50 °C
- **Humidity Range:** 0–100%
- **Chemical Exposure:** Use of chemical products may affect performance
- **UV Protection:** Yes

Instructions of use

1. **Position the grip belt** on the **tube**, aligning it with the **size indicators (S, M, L)** marked on the surface.
2. **Adjust the diameter** by selecting the appropriate **hole on the buckle** and securing it with the **curved tip**.
3. **Place the tree** within the grip belt and **fasten the strap securely** around the trunk.
4. **Ensure the system is properly tightened** and the **tree is fully stabilized**.
5. **Tool-free installation** makes the system ideal for **high-volume operations**.
6. **Once the tree is removed**, the **AGILO system remains in place**, ready to support the next tree.

Stocking conditions

- Stock the boxes in a dry and fresh place

- The product specifications are subject to change without notice to improve reliability, function or design or otherwise.
- It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

Replaces the Ed/Rev. N°- dated: -